

R11 Above ground foul drainage systems
315 FLOOR DRAINS

- **Manufacturer: Schlüter-Systems Ltd**, Units 3-6 Bardon 22, Beveridge Lane, Coalville, Leics. LE67 1TE. Tel: 01530 813396, Fax: 01530 813376. E-mail: technical@schluter.co.uk or sales@schluter.co.uk. Web: www.schluter.co.uk
- **Product reference: Schlüter®-KERDI-LINE G3** is a component linear drainage system for floor level showers with a 50mm water seal and a minimum flow rate of 0.4 l/s (single outlet). The system consists of a stainless steel channel, with channel support and a choice of grate and frame options. Available with a horizontal outlet and is supplied with an easily maintained odour trap for internal applications. Install in line with manufacturer's recommendations, refer to **Schlüter®-Systems Technical Data Schlüter®-KERDI-LINE-G3**.
The system can be combined with the Schlüter®-KERDI-SHOWER-L, which is a pressure resistant polystyrene sloped board system.
- **Floor finish:** Suitable for use with tile or stone coverings.
- **Body type:** Two part channel and drain casing.
 - Material: V4A Stainless steel (Material no. 1.4404) channel with ABS drain casing and odour trap.
 - Outlet: Offset left or right (Centre of offset 200 mm from end of channel flange. Outlet can be front or rear facing).
- **Technical specifications:**
 - Drain height = 78 mm
 - 40 mm solvent weld horizontal outlet
 - Pre-applied Schlüter-KERDI waterproofing collar.
 - Suitable for use in perimeter or intermediate floor locations.
 - Odour trap accessible and cleanable from above.
 - Odour trap shutter lock gate clamp for watertight seal.
 - Load rating class = K3
- **Compliance information:**
 - Tested in accordance with BS EN 1253, BS EN 274 and Building Regulations Approved Document H.
- **Accessories:**
 - Choice of grate options: A, B, DG3, Floral, Curve and Pure, refer to Schlüter-Systems brochure.
 - Schlüter-KERDI-COLL sealant adhesive to adhere waterproof collar to Schlüter-Systems waterproofing membranes.